INOK1100F Automatic Kjeldahl Nitrogen Protein Analyzer

INOK1100F Automatic Kjeldahl Nitrogen Protein Analyzer is an automatic device integrating distillation and titration system and it is designed based on classic Kjeldahl nitrogen determination method. It's equipped with the latest core control system, powerful automation and high-quality components; can easily achieve automatic waste discharge and cleaning of digestion tubes and titration cups, control steam supply and real-time detection of condensation temperature. High-accuracy charging pump and titration system ensure test results accuracy, and multiple fluid level detection gives smooth test process.



Characteristics

- Automatic distillation, titration, calculation, printing, drain and cleaning function, safety and saving-time.
- Visibletitration cup design gives operatorreal-time control of the whole test process.
- Steam flow is controllable, satisfying differenttest requirements.
- Regent barrel enjoys fluid absence warning function, ensuring smooth test going.
- High-precision charging pump and titration system ensure test results accuracy.
- Large LCD touch screen gives visual operationand abundant information, enabling user to have a good commandof it.
- USB or RS485 interface is optional for PC connection.
- Distilled liquid temperature is detected real time. Emergency stop against temp anomaly.
- Double distillation modelmeets different experiments, to retard the speed of acid-base reaction.
- Digestion tube fast drain function is used to avoid operator touch distilled hot reagents, protecting operators.
- · Printer is built in.

Complete microcomputer control

Automatic completion of distillation, titration, calculation, printing, waste discharge and multiple protections, i.e.failure self-detection, hints of condensed water shortage, displacement of safety door and digestion tube and so on.

Large LCD Touch Screen Panel

Large LCD touch screen gives visual operation and abundant information, enabling user to have a good command of it.

INO**K1100F**

Complete compatible design Compatible with congeneric products perfectly

Performance advantage

- Compatible with φ 42mm digestion tube
- Titration while distillation, enhance the efficiency rapidly.
- User friendly design, color touch screen, easy for operating
- Faster ARM system, faster operating rate
- Digester model SH220F and SH420F is matching K1100F, with $\phi42$ digestion tube



Technical data

Measuring range	0.1mg \sim 240mg N
Analysis time	$3\sim$ 8min/sample
RSD	≤0.5%
Recovery	≧99.5%
Burette volume	1.0µL/step
Sample capacity	solid≦5g/sample, liquid≦20mL/sample
Water consumption in the distillation process	1.5L/min
Data storage capacity	1800 groups
Power supply	220VAC±10%, 50Hz
Power	2Kw
Net weight	38Kg
Dimensions	455mm×391mm×730mm